

AN2723T

3 Mega Ultra Mini IR IP Dome



SONY Exmor 

Model Number	AN2723T
Image Device	Sony Exmor 3mega Pixel cmos sensor
Video Resolution	2048*1536
Lens	Fixed lens
IRIS	Fixed Iris
IR LED	4pcs IR LED (about 10 meter IR distance)
ICR	Mechanical ICR
IP Module	
Video	
Video Encoder	H.264 and MJPEG simultaneously
Video Profile	Multi-streaming simultaneously
Frame Rate	3Mega up to 30fps (NTSC)/ 25fps (PAL)
Image Setting	AE, AWB 3D Noise reduction Color, brightness, sharpness, contrast, Mirror / Flip Privacy Masks Extra WDR
Streaming	Simultaneously multi- stream Streaming over UDP, TCP, HTTP, or HTTPS M-JPEG streaming over HTTP (server push) Controllable frame rate and bandwidth
Audio	



www.a-mtk.com
sales@a-mtk.com
 TEL: +886-2-82269855
 FAX: +886-2-82269800

Audio Encoder	RTSP: G.711 64kbps, G.726 32kbps, AAC (option, by request)
Network	
Supported Protocols	IPv6, IPv4, TCP, UDP, HTTP, HTTPS, SMTP, FTP, NTP, DNS, DDNS, DHCP, DIPS, ARP, Bonjour, UPnP, RTSP, RTP, RTCP, IGMP, PPPoE, 3GPP, Samba, ICMP, SNMP
Security	Password protection, IP address filtering, HTTPS encrypted data transmission, user access log
Users	20 simultaneous unicast users
Ethernet	10/100M auto negotiation
System Integration	
SDK	ONVIF 2.0 and above Open API for software integration
Event Detection	<ul style="list-style-type: none"> ● Motion detection ● Audio detection ● Camera tampering ● Cross line ● Sensor input (DI) ● NFR (Network Failure)
Alarm Events	<ul style="list-style-type: none"> ● File upload via FTP or email ● File upload via Samba to NAS ● Notification via email, HTTP, and TCP ● Alarm output (DO) ● Push notify to smart phone apps ● Save to local mSD card
Video Buffer	Pre- and post- alarm buffering
General	
Power Supply	12V DC Power over Ethernet (PoE)
PoE	IEEE 802.3af class 3
I/O	RJ-45 10Base-T/100Base (PoE) 12V DC power input External MIC input External audio output DI (sensor) x 1 DO (alarm) x 1 mSD card
Indication LED	Green and orange LEDs
Operating	0°C to 40°C



www.a-mtk.com
sales@a-mtk.com
TEL: +886-2-82269855
FAX: +886-2-82269800

Temperature	
Operating Humidity	20% ~ 80% (non-condensing)
Viewing System	
OS	Windows® 7 , 8, 8.1, Win 10
Browser	IE 9.0 or latter
Software	
Search & Installation	IP Wizard II
Bundled NVR Program	64ch. SecuGuard™ <ul style="list-style-type: none">* 64ch. multi-channel supports Tri-decoder* 16ch. video playback (simultaneously)* Smart & scrollable digital zoom. Snapshot and edit* Motion, DI, Scheduler recording* Fast rewind and forward (MPEG4, H.264, MJPEG rewind)* 32x24 motion detection grids* Smart search (by time, by motion)* E-MAP* Event schedule setting* Remote service* Camera tampering
Bundle Mobile Phone APPS	SecuAngel (Android) and iVanguard (iOS)

※ The product design and dimensions may change without previous notice for improvement of performance.