

Model: AH5911T-40x

5 Mega pixel speed dome IP camera



Features

- H.265, H.264 , MJPEG
- Ethernet (100Base-TX)
- Smart remote 40x zoom/focus
- Sony sensor 5MP resolution
- ONVIF compatible



A - M T K C o . , L t d .

Tel: +886-2-82269855

www.a-mtk.com

sales@a-mtk.com.tw

Camera	
Sensor	SONY Exmor™ 1/2.8" CMOS sensor
Effective pixel	5MP pixel
Lens	f:4.3-170mm auto focus lens
Fcous	Auto/Manual
IR LED	Smart IRE LED, 200m
Day/night	Mechanical ICR, Auto/Manual/Schedule
Min Illumination	Color: 0.01 lux B/W: 0 lux (IR LED on)
Image	
Cdoes	H.265/H.264 MP/MJPEG
FPS	30 FPS @ all resolution
Exposure	Auto/manual Auto/Auto indoor/Manual BLC WDR
Settings	AE, AWB, AGC Shutter speed 1~1/10K second Color, Hue, Brightness, Contrast, Sharpness 2D/ 3D denoise Mirror/Flip EIS
OSD	Text, Date
Audio	
Codec	G.711, G.726
Dual channel	line in/ line out
Internet	
Protocol	IPv4/v6, TCP, UDP, DHCP, PPPoE, HTTP, HTTPS, DNS, DDNS, NTP, RTP, RTSP, SMTP, FTP, IGMP, ICMP, ARP, UPnP, QoS, SNTP
Cyber security	IPfilter, password, HTTPS encryption, user log
Ethernet	10M/100M Auto negotiation
System	
Integration	ONVIF Profile S, G, T compatible
Event	Motion detection Digital input Internet breakdown
Trigger event	FTP and email upload HTTP notify Digital output
PTZ	
Default point	256 point
Pan/tilt	Horizontal 360° Vertical-20°~100°
Manual speed	Horizontal 0.1-90°/sec Vertical 0.1-55°/sec
Suto speed	Horizontal 300°/sec Vertical 300°/sec
General	
Power	AC24V , UPoE
Consumption	50W 62W with heater & IRLED

Connector	RJ-45 10BASE-T/100BASE-TX AC 24V Digital inputx4 Digital outputx2 Audio line in x1 Audio line out x 1 mSDslot(SHDC/ SDXC)
Casing	Aluminum
Heater	Equipped
Operation Temp	-40°C to 50°C (with heater)
Operation humid	10% ~ 90%(non-condense)
Browser	
OS	Windows® 7, 10, 11
Browser	IE 9.0, Google chrome
Certification	EMC: CE, FCC, IP66